

NEW
SORGENTI SPOT
LEXAR



Ø 50 x 55 mm - 25 g

110°		OUTPUT 360°	OUTPUT 90°				
GU10	9 W = 50 W	1.000 lm	750 lm	3000K	LX110-091030 NEW	10/50	6,00 €
				4000K	LX110-091040 NEW		
				6500K	LX110-091060 NEW		

GU10 220-240 V IP20 110°



Ø 50 x 46 mm - 26 g

60°		OUTPUT 360°	OUTPUT 90°				
GU5.3	5 W = 40 W	400 lm	350 lm	3000K	LX60-065330	10/50	6,00 €
				4000K	LX60-065340		
				6500K	LX60-065360		
	6,5 W = 50 W	500 lm	450 lm	3000K	LX60-085330	10/50	6,50 €
				4000K	LX60-085340		
				6500K	LX60-085360		

GU5.3 12 V AC/DC IP20 60°

TECHNICAL NOTES

ALIMENTAZIONE CON TRASFORMATORI ELETTROMAGNETICI E NON ELETTRONICI
POWER SUPPLY WITH ELECTROMAGNETIC AND NON-ELECTRONIC TRANSFORMERS

Disponibili in diverse temperature di colore luce, sono adatte sia per l'illuminazione d'accento che per quella generica.
Available in different color temperatures and suitable for both accent and general lighting.