

T5 FHO Luxline Plus

24W/T5/865 FHO
0002774



Product features

- T5 FHO Luxline Plus



PRODUCT OVERVIEW

Product name	24W/T5/865 FHO
Technology	Fluorescent
Watt (Rated) (W)	24
Lamp shape	Tube, double-ended
Cap/Base	G5
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000108
E-number FI	4944505
E-number SE	8356538
E-number Norway	3800986
Useful luminous flux (Fuse)	1800
Luminous flux (lm)	1600
Rated lamp efficacy 100h 50Hz at 35°C (lm/W)	68
Colour temperature (K)	6500
Light colour	Daylight
Colour Code	865
CRI (Ra)	85
Colour Variation Initial (SDCM)	SDCM5
Photobiological Risk Group	Not applicable
Wattage (W)	24.00
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Average life (Nominal) (h)	24000
Product EAN number	5410288027746

DATA TABLE

General data

Product name	24W/T5/865 FHO
Technology	Fluorescent
Watt (Rated) (W)	24
Lamp shape	Tube, double-ended

T5 FHO Luxline Plus

24W/T5/865 FHO
0002774

Cap/Base	G5
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000108
E-number FI	4944505
E-number SE	8356538
E-number Norway	3800986

Optical data

Useful luminous flux (Fuse)	1800
Luminous flux (lm)	1600
Luminous flux (Rated) (lm)	1600
Luminous flux (Nominal) at 35°C (lm)	1800
Rated lamp efficacy 100h 50Hz at 35°C (lm/W)	68
Ambient temperature for maximum luminous flux (°C)	35
Colour temperature (K)	6500
Light colour	Daylight
Colour Code	865
CRI (Ra)	85
Colour Variation Initial (SDCM)	SDCM5
Adjustable chromaticity	N
Luminous Intensity (cd)	Not Applicable
Photobiological Risk Group	Not applicable
Rated lumen maint. factor (%) at 2000 h 50Hz	0.97
Rated lumen maint. factor (%) at 4000 h 50Hz	0.95
Rated lumen maint. factor (%) at 6000 h 50Hz	0.93
Rated lumen maint. factor (%) at 8000 h 50Hz	0.92
Rated lumen maint. factor (%) at 12000 h 50Hz	0.91
Rated lumen maint. factor (%) at 16000 h 50Hz	0.90
Rated lumen maint. factor (%) at 20000 h 50Hz	0.88

Electrical data

Wattage (W)	24.00
Current (A)	0.300
Primary Supply/Product voltage - min (V)	67.0
Primary Supply/Product voltage - max (V)	83.0
Control gear required	Yes
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	300

T5 FHO Luxline Plus

24W/T5/865 FHO
0002774

Lamp Energy Label (class)	G
kWh per 1000 hours burning time	26

Lifetime data

Average life (Nominal) (h)	24000
Average life (Rated) (h)	24000
Rated survival factor (%) at 2000 h 50Hz	0.99
Rated survival factor (%) at 4000 h 50Hz	0.98
Rated survival factor (%) at 6000 h 50Hz	0.96
Rated survival factor (%) at 8000 h 50Hz	0.94
Rated survival factor (%) at 12000 h 50Hz	0.93
Rated survival factor (%) at 16000 h 50Hz	0.90
Rated survival factor (%) at 20000 h 50Hz	0.84

Physical data

Nominal Product Length (mm)	550.0
Nominal Product Diameter (mm)	16
Max. Length base to base (mm) - A	549.0
Length base to pin Min-Max (mm) - B	553.7-556.1
Max. Lamp Length (mm) - C/L	563.2
Max. Lamp Diameter (mm) - D	17.0
Weight (kg)	0.043

Packaging


Product EAN number	5410288027746
Packaging single length / height (cm)	56.4
Packaging single width (cm)	1.9
Packaging single depth (cm)	1.9
DUN14 (outer)	15410288027743
Units per outer package	25
Packaging outer length / height (cm)	57.8
Packaging outer width (cm)	10.5
Packaging outer depth (cm)	10.5

Safety data


Lamp mercury content (mg)	2.30
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Suitable for household illumination	Yes

PHOTOMETRY

T5 FHO Luxline Plus
24W/T5/865 FHO
0002774



TECHNICAL DRAWINGS



0002774



24
kWh/1000h




2019/2015

SYLVANIA

T5 FHO Luxline Plus
24W/T5/865 FHO
0002774



0002774



24
kWh/1000h



2019/2015